

SealArm Tape FB 300-M

(Formerly known as MYK Caro FB 300 (M))

Joint Tape



TECHNICAL DATA SHEET

Product Description

SealArm Tape FB 300-M is water impermeable Joint Tape. This tape is easy to handle and perfectly combines to the waterproofing systems AquaArm Saniflex, AquaArm WPU 1K, AquaArm Coat WAC, and AquaArm TG etc.

Uses

SealArm Tape FB 300-M is used for the safe bridging of connecting joints and expansion joints in surface waterproofing coats at moderate water loads.

Application Methodology

Instructions for Use:

The waterproofing material is to be applied over the joints to be bridged at least 2 cm wider than the joint tape's width. The joint tape is laid onto the fresh layer, pressed on it evenly and wrinkle-free and then overworked with the waterproofing material except for the expansion zone. Joints are to be fully bond.

Not suitable for underwater use and as bridge for building expansion joints.

Technical Data

Material	Special TPE-coated Modified Polyester non- woven
Colour	Lt grey-coated
Total thickness	Approx. 0.63 mm
Material weight	Approx. 27 g/m
UV-resistant	Yes (500 hrs)
Width Total	120 mm
Width of coating	70 mm
Length	50 m
Age-resistant	Yes
Service temperature	30° to + 90 °Celsius
Elongation	Max. 122 %
Resistance to Water pressure	>1.5 bar
Breaking load longitudinal (DIN EN ISO 527-3)	≥ 80 N / 15 mm
Breaking load lateral (DIN EN ISO 527-3)	≥ 20 N / 15 mm
Tear Strength longitudinal (DIN EN 1230-2)	32 N
Tear Strength lateral (DIN EN 1230-2)	135 N

SealArm Tape FB 300-M

(Formerly known as MYK Caro FB 300 (M))

Joint Tape

Packaging

Width 12 cm Length 50 m,
4 rolls in one per box

Storage and Shelf Life

Cool and dry, protect against sunlight,
Use within 24 months after receipt.



TECHNICAL DATA SHEET

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

MYK Arment Private Limited
(Formerly Known as MYK Schomburg India Pvt.Ltd)
8-2-703/A, 3rd Floor, Leela Gopal Towers, Road No. 12, Banjara Hills, Hyderabad -500 034
Tel: +91 40 6816 0001 | Email: myk@mykarment.com | www.mykarment.com