

ReArm Stone Guard - W

(Formerly known as MYK STONE GUARD W2S)

Water Repellent



TECHNICAL DATA SHEET

Product Description

ReArm Stone Guard–W water Repellent is a water diluted solution of alkali alkyl siliconate designed to impart water repellency to a wide variety of surfaces.

Uses

- For moisture protection of facades or for inclined areas
- Porous concrete, bricks, lime sand stone
- Clinker Facades Stones, Light concrete etc.

Features and Benefits

- Leaves the interior dry in all weather conditions
- Prevents fungus and moss growth
- Good penetration capacity
- long lasting and durable impregnation to facades
- Nonflammable

Application Methodology

Step no 1: Surface Preparation

The base must be sound, clean, should be free from oil, grease and from loose particles .The plaster should be at least 14days old and the cracks and other defective spots should be rectified before impregnating

Step no 2: Application

Surfaces to receive the water- soluble silicone should be lightly dampened immediately prior to application. This water-soluble silicone does not wet surfaces that have been previously treated with silicone or another repellent treatment. When spraying ReArm Stone Guard–W Water Repellent, great care should be taken to protect nearby vegetation articles from over spray. The material is very caustic will damage or kill vegetation and will stain or etch glass, plastic, aluminum and most metals .If contact does occur ,wash immediately with water. For use on bricks, sand stone, limestone, and ceramics.

Technical Data

Specific gravity at 25°C	1.04 - 1.06
pH	Approx 13

ReArm Stone Guard - W

(Formerly known as MYK STONE GUARD W2S)

Water Repellent

Coverage

2 Sq. mtrs per Kg (depends on the porosity)

Packaging

5 & 20 Kg Pack

Storage and Shelf Life

Store in cool dry place

24 months from date of manufacturing.

Health & Safety

Use of hand gloves is necessary while mixing the product in case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.



TECHNICAL DATA SHEET

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.