Admixture & Surface Treatment

Armix Plast 111

(Formerly known as MYK PLAST 111)

High Performance Concrete Admixture



TECHNICAL DATA SHEET

Product Description

Armix Plast 111 is supplied as a brown colour liquid. It has been specially formulated to give high workability or to produce high quality concrete with better density and reduced permeability.

Uses

- Suitable for high performance concrete
- To produce pump able concrete
- To increase workability
- To improve cohesion
- Minimizing segregation and give better finish
- Chloride free
- Safe for use in pre stressed and reinforced concrete

Features and Benefits

- Improved workability
- Increased strength
- Increased quality
- Higher cohesion Risk of segregation and
- Minimized bleeding and segregation.
- Water Reducer cum plasticizing concrete Admixture

Application Methodology

Application:

Armix Plast 111 directly can be added to the concrete during the process of mixing @ 100-125ml per 1 bag of cement.

Technical Data

Appearance	Brown colour liquid
рН	>7.0
Specific gravity	Approx.1.200

Coverage

100-125 ml per 1 bag of cement

Note: - For special cases site trials to be conducted before being used.

Packaging

125 ml, 1, 5, 10 & 20 Lit Pack

Storage and Shelf Life

Store in cool dry place

Shelf Life: 24 months from date of manufacturing

Health & Safety

Armix Plast 111 is non-toxic. Any splashes on the skin should be washed immediately with water. Splashes to the eyes should be washed immediately with water and medical advice should be sought.



Ver/6/Oct 2021 1 of 2

Admixture & Surface Treatment

Armix Plast 111

(Formerly known as MYK PLAST 111)

High Performance Concrete Admixture



Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

Ver/6/Oct 2021 2 of 2