

SealArm Corner Tape

(Formerly known as MYK Caro FB 300 (M))

Sealing Tape for general requirements



TECHNICAL DATA SHEET

Product Description

SealArm Corner Tape is water impermeable Joint Tape. This tape is easy to handle and perfectly combines to the water proofing systems AquaArm SaniGuard, AquaArm SuperFlex, AquaArm FlexiCoat, AquaArm WPU Ultra, AquaArm RightCoat, AquaArm WonderCoat, AquaArm TopGuard etc.

Uses

SealArm Corner Tape is used for the safe bridging of connecting joints and expansion joints in surface waterproofing coats at moderate water loads.

Application Methodology

Instructions for Use

The waterproofing material is to be applied over the joints to be bridged at least 2 cm wider than the joint tape's width. The joint tape is laid onto the fresh layer, pressed on it evenly and wrinkle-free and then overworked with the waterproofing material except for the expansion zone. Joints are to be fully bond.

Not suitable for underwater use and as bridge for building expansion joints.

Technical Data

Material	Special TPE -coated Modified Polyester non-woven
Colour	Lt grey-coated
Total thickness	Approx. 0.63 mm
Material weight	Approx. 27 g/m
Width of coating	70 mm
Length	50 m,
Width Total	120 mm
UV-resistant	Yes (500 hrs)
Age-resistant	Yes
Service temperature	30° to + 90°Celsius
Elongation	Max. 122 %
Resistance to Water pressure	>1.5 bar

SealArm Corner Tape

(Formerly known as MYK Caro FB 300 (M))

Sealing Tape for general requirements

Packaging

Width 12 cm Length 50 m,
4 rolls in one per box

Storage and Shelf Life

Cool and dry, protect against sunlight,
Use within 24 months after receipt.



TECHNICAL DATA SHEET

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

MYK Arment Private Limited
8-2-703/A, 3rd Floor, Leela Gopal Towers, Road No. 12, Banjara Hills, Hyderabad -500 034
Tel: +91 40 6816 0001 | Email: myk@mykarment.com | www.mykarment.com

