

# SealArm Joint Tape

(Formerly known as MYK ASO-Joint-Tape-2000)

Sealing Tape for general requirements



## TECHNICAL DATA SHEET

### Product Description

SealArm Joint Tape is a new type of composite material, expandable, tensile, stable, waterproof but allows intrusion of water vapour diffusion pores. It guarantees the fast drying of water-containing tile adhesives and water proofing layers. SealArm Joint Tape is highly resistant to aggressive substances. SealArm Joint Tape is a product according to the ZDB-leaflet "Instructions for the application of waterproofing layers in composite with covering and paneling of tiles and panels for interior and exterior use."

### Uses

For the waterproofing of expansion and dilatation joints in sealing layers of AquaArm SaniGuard, AquaArm SuperFlex, AquaArm FlexiCoat, AquaArm WPU Ultra, AquaArm RightCoat, AquaArm WonderCoat, AquaArm TopGuard etc

### Application Methodology

#### Instructions for Use

SealArm Joint Tape is pressed on joints over surfaces that are treated with respective waterproofing materials. The surface sealant (at least 2 cm in width) and wider than the sealing tape is to be applied on both sides of the bridged joints. The Joint tape is to be applied on the new surface, evenly placed without creasing. Then the sealant can be applied. The area of the settlement joint (for the subsequent elastic joint application) should be kept free from sealant. The edges of the Joint Tape are to be bonded with an overlap of at least 5 cm and with the sealant, covering the complete surface without creasing.

For designated areas requiring specialized care, eg: for Inner and outer corners we recommend safe application with SealArm Joint Tape Corners.

#### Surfaces

For all types of surfaces in fields of construction, which are to be tiled or for waterproofing layers which have been skillfully prepared. Fine non-continuous cracks on the surface face which are minimal (below 0, 1 mm) can be tolerated.

#### Technical Data

Basis	Binding material Fleece - membrane-fleece
Colour	White
Thickness	0.3 mm
Allowance of Initial movement	Max. 30% of the joint width Composite gripping
Tension	At least 0.5 N/mm <sup>2</sup>
For designed Areas with	Inner corners of 12 cm at 90°C Outer corners of 12 cm at 90°C

## SealArm Joint Tape

(Formerly known as MYK ASO-Joint-Tape-2000)

Sealing Tape for general requirements



### TECHNICAL DATA SHEET

#### Packaging

1M Width 25 Meter Rolls  
Width 12 and 20 cm Rolls of 10 and 50 m  
Boxes of 500 m in total

#### Storage & Shelf life

24 months when stored cool and dry protected from sunlight and weather influences

#### Annotation

Only approved Construction Techniques are to be applied. Joints which are to be sealed with SealArm Joint Tape are to be protected against any mechanical influences accordingly. We recommend SealArm Joint Sealing-Tape for walls or Floor connections in soiled earth areas and for expansion joints in structures.

#### Product Categories Available



#### Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

MYK Arment Private Limited  
8-2-703/A, 3rd Floor, Leela Gopal Towers, Road No. 12, Banjara Hills, Hyderabad -500 034  
Tel: +91 40 6816 0001 | Email: myk@mykarment.com | www.mykarment.com

