

ReArm Insta Plug

(Formerly known as MYK FIX 10-S)

Fast Settling Cement



TECHNICAL DATA SHEET

Product Description

ReArm Insta Plug is chloride free quick setting cement with immediate start of hardening after addition of water.

Uses

- Subsequent sealing of surface leakage, water leaks and damp areas in cellars, manholes, tunnels, etc.
- Against water and pressure water from the backside or front side.

Features and Benefits

- Instant arrest of the leakage area

Application Methodology

Surface Preparation

The surface has to be loadable and clean. Paints, brittle plaster, screed etc., have to be removed up to the solid ground (concrete, masonry). Dry areas have to be wetted. For interior sealing light weight blocks have to be pre-treated with a loadable cement plaster. Sealing of aerated concrete blocks or elements is not possible.

Instructions for use

Sealing of leakage

Leaking parts in sealed surfaces may be closed by pressing Insta plug in dry form or mixed with water into the leakage. Insta plug is to be pressed into the leak.

Technical Data

Basis	Cement, additives
Colour	Cement grey
Bulk Density	1.2 gm/cc
Application temperature	+ 5 ⁰ C to + 30 ⁰ C
Start of setting	Immediately after water addition

ReArm Insta Plug

(Formerly known as MYK FIX 10-S)

Fast Settling Cement



TECHNICAL DATA SHEET

Consumption

Depends on the area

Packaging

1 Kg Pouch & 12 Kg Bag

Storage and Shelf Life

Store in cool dry place
12 months from date of manufacturing.

Health & Safety

Use of hand gloves is necessary while mixing the product in case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.