

AquaArm Duct Tape

Double side overlapping tape
Self-adhering waterproofing tape for structure
details treatment



TECHNICAL DATA SHEET

Product Description

A cold applied, flexible, synthetic self- adhesive tape based on pressure-sensitive adhesive(PSA), middle layer reinforced with high polymer film, the two side is coated with PSA and protected by release film which gives it perfect anti-UV performance.

Application Methodology

- Substrate must keep clean, no oil or dust.
- Application temperature above + 5⁰C.
- Application will be forbidden at rainy day.
- Liquid water will dramatically decrease bonding performance of adhesive.

Precautions

- AquaArmDuct tape has tendency to debond in hot atmosphere or if exposed in sunlight. Hence in such area recommended to use this tape two time to avoid de bonding till concreting is done.(Not suitable for hot weathering)

Technical Data

Item	AquaArm Duct Tape
Thickness	0.8mm (-10% + 10%)
Width	100mm
Length	30m
Roll size	100mm*30m
Bottom	PSA with release film
Top	PSA with release film
Appearance	Rolls
Color	White
Roll weight	2.6kg
Peel strength	≥ 1000 N/m



Waterproofing Systems

AquaArm Duct Tape

Double side overlapping tape
Self-adhering waterproofing tape for structure details treatment

Packaging

- 30m/roll, 6 rolls packed into cartons
- AquaArm Duct Tape:-100MM x 30M

Storage and Shelf Life

- Sealed and stored in a cool and dry place, avoiding direct sun and rain exposure.
- Shelf life is 12 months from manufactured date.



TECHNICAL DATA SHEET

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

MYK Arment Private Limited
8-2-703/A, 3rd Floor, Leela Gopal Towers, Road No. 12, Banjara Hills, Hyderabad -500 034
Tel: +91 40 6816 0001 | Email: myk@mykarment.com | www.mykarment.com